

## 詳細說明 Specification

機械規格 Specification	MTK-60x3	MTK-80x3
機台出力 Capability (ton)	60	80
行程 Stroke (mm)	120	
上升速度(mm/sec) Cylinder lifting speed	117	110
下降速度(mm/sec) Cylinder descending speed	141	130
操作壓力(kg/cm <sup>2</sup> ) Operating pressure	20~210	
電壓 Voltage	AC 220/380	
馬達 Motor (HP)	10 HP	10 HP/ 15 HP
工作方向 Operating type	直立式 Vertical	
工作模式 Operating mothod	自動/手動 Auto/Manual	
油容量(l) Oil Capacity	1000	1000
重量(kg) Weight	4000KG	4300KG

## 多軸高速沖孔機 / MTKx3

Punching Press Machine

Model / MTKx3 Series

MTKx3 Series - MTK60x3 / MTK80x3



1. 多軸高速沖孔機採用PISTON高壓泵浦，高效率、省電、省工時，適合連線作業，省空間，是用手工具加工製造，汽機車零件沖孔加工等。
2. 機械亦可依使用者工作條件量身訂作。

1. Vertical and high strength structure. Available for punching, pressing, leveling and shaping. High efficiency and energy saving
2. Machine specification also can be designed by optional requirement of the users.