

詳細說明 Specification

機械規格 Specification	YS-600-2 雙軸	YS-800-2 雙軸	YS-1000-2 雙軸	YS-1200-2 雙軸	YS-1600-2 雙軸
行程 Stroke (mm)	600	800	1000	1200	1600
上升速度(mm/sec) Cylinder lifting speed	0~329	0~329	0~329	0~329	0~306
下降速度(mm/sec) Cylinder descending speed	0~144	0~144	0~144	0~144	0~122
操作壓力(kg/cm ²) Operating pressure	30~140				
電壓 Voltage	AC 220/380				
馬達 Motor (HP)	5HP*2	7.5HP*2	7.5/10HP*2	10HP*2	15HP*2
工作方向 Operating type	直立式 Vertical				
工作模式 Operating method	自動/手動/半自動 Auto/Manual/Semi Auto				
油容量(l) Oil Capacity	600	800	800	800	1100
重量(kg) Weight	4500KG	5000KG	5500KG	6000KG	7500KG
模寬(mm) Mold Size (L)*(W)	430*350*2				
工作台尺寸(mm) Work Table Size (L)*(W)	1600*550				2000*550
外型規格(mm) Size	2150*2120*2180	2150*2120*2380	2150*2120*2780	2150*2120*3200	2450*2800*3980

雙軸平面拉床 / YS-2

Hydraulic Broaching Machine

Model / YS-2 Series

YS SERIES - YS600-2 / YS800-2 / YS1000-2 / YS1200-2 / YS-1600-2



- | | |
|--|--|
| <ol style="list-style-type: none"> 1. 適合各種零件之外徑齒不規則外型拉削，一次完成所需尺寸，省時省工。 2. 速度快、精度高、定位準確。 3. 壓力、速度均可依所需工件自由調整。 4. 模具加工，送料均可依工件條件量身訂作。 5. 易操作、省工時、加工精度高。 6. 主要適用於汽機車零配件、五金配件、手工具等... 配件之內孔精密拉削。 | <ol style="list-style-type: none"> 1. Suitable for external and any unequal shape broaching. Processing for all kind of required size in one time. 2. High speed & precision, precise positioning. 3. Pressure & speed are adjusted by work pieces requirement. Customer made machine / mold are acceptable. 4. Easy operation, saving time, high processing precision. 5. Broaching applications for auto mobile components, hardware components, variable tooling components...and so on... |
|--|--|