

詳細說明 Specification

機械規格 Specification	YS-600 單軸	YS-800 單軸	YS-1000 單軸	YS-1200 單軸	YS-2000 單軸
行程 Stroke (mm)	600	800	1000	1200	2000
上升速度(mm/sec) Cylinder lifting speed	0~329				
下降速度(mm/sec) Cylinder descending speed	144				
操作壓力(kg/cm ²) Operating pressure	30~140				
電壓 Voltage	AC 220/380				
馬達 Motor (HP)	5HP	7.5HP	7.5/10HP	10HP	15/20HP
工作方向 Operating type	直立式 Vertical				
工作模式 Operating method	自動/手動 Auto/Manual				
油容量(l) Oil Capacity	450	450	500	500	500
重量(kg) Weight	2500KG	2500KG	3800KG	3800KG	5500KG
模寬(mm) Mold Size (L)*(W)	500*350				
工作台尺寸(mm) Work Table Size (L)*(W)	1270*520				
外型規格(mm) Size	1740*1900*2320	1740*1900*2520	1740*1900*2920	1740*1900*3420	2540*2350*4900

單軸平面拉床 / YS

Hydraulic Broaching Machine

Model / YS Series

YS Series - YS-600 / YS-800 / YS-1000 / YS-1200 / YS-2000



- 適合各種零件之外徑齒不規則外型拉削，一次完成所需尺寸，省時省工。
 - 速度快、精度高、定位準確。
 - 壓力、速度均可依所需工件自由調整。
 - 模具加工，送料均可依工件條件量身訂作。
 - 易操作、省工時、加工精度高。
 - 主要適用於汽機車零配件、五金配件、手工工具等... 配件之內孔精密拉削。
- Suitable for external and any unequal shape broaching.
 - Processing for all kind of required size in one time. High speed & precision , precise positioning.
 - Pressure & speed are adjusted by work pieces requirement.
 - Customer made machine / mold are acceptable.
 - Easy operation, saving time , high processing precision.
 - Broaching applications for auto mobile components, hardware components, variable tooling components...and so on...